

Datasheet Conveyor Belt




**NITTA CORPORATION
OF HOLLAND**

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
2 RF
- **Nitta Japan code:**
CC-16DK



Construction: 2 plies polyester, rigid

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	Fabric	PVC	Fabric	
Thickness:	-		-	mm (approx.)
Colour:	-	White	-	
Hardness:	-		-	
Profile:	-		-	

Total thickness:	1,8	mm (approx.)
Weight:	1,9	kg/m ² (approx.)
Max. width:	3000	mm
Belt support:	Sliderbed (Rollers), Flat	

Rating at 1% elongation:	10	N/mm
Advised pretension:	4 - 7	N/mm
Maximum allowable tension:	20	N/mm
Temperature range:	-10 to +90	°C

Minimum pulley diameters:		
Flexing:	20	mm
Backflexing:	20	mm

Special approval: FDA, 10/2011/EC + amendments

Applications:

- In the wood and board industry
- Bobbin transport in the textile industry
- In the paper and cardboard industry
- Dough handling in bakeries
- Accumulation belt

Date of issue 08-04-2014-1

Your Partner In Belting Solutions

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nittacorporation.com