



DATA SHEET

CONVEYOR BELT

- ▶ **NITTA BELT TYPE:**
2 RF 372 LRB IM 55°
- ▶ **Nitta Japan code:**
-



CONSTRUCTION: 2 plies polyester, rigid

TOP COVER:	Material:	PVC	
	Top thickness:	2,0	mm (approx.)
	Colour:	blue	
	Hardness:	55A	
	Profile:	LRB	

BOTTOM SIDE: Impregnated fabric

Total thickness:	5,4	mm (approx.)
Weight:	4,6	kg/m ² (approx.)
Max. width:	2000	mm
Belt support:	sliderbed, (rollers) flat	

Rating at 1% elongation:	10	N/mm
Advised pretension:	4-7	N/mm
Maximum allowable tension:	16	N/mm
Temperature range:	-10 to +90	°C

Minimum pulley diameters:		
Flexing:	60	mm
Backflexing:	120	mm

Special approval: FDA, 10/2011/EC + amendments

Applications: Inclined or declined conveyors
Heavy duty applications
Conveyor belt for the food industry
Blue colour makes possible product contamination visible
Oil and grease resistant

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nitta.nl



**NITTA CORPORATION
OF HOLLAND B.V.**

Berenkoog 25 - 1822 BH Alkmaar - Phone +31.72.562 22 34 - Fax +31.72.561 32 38 - E-mail sales@nitta.nl - www.nitta.nl

Date of issue: 22-07-2013