

Datasheet Conveyor Belt



**NITTA CORPORATION
OF HOLLAND**

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
2 R 371/371 M
- **Nitta Japan code:**



Construction: 2 plies polyester, rigid

	TOP COVER	INNER LAYER	BOTTOM SIDE	
Material:	PVC	PVC	PVC	
Thickness:	0,7		0,7	mm (approx.)
Colour:	Blue	Blue	Blue	
Hardness:	65 Shore A		65 Shore A	
Profile:	-		matt	

Total thickness:	3,1	mm (approx.)
Weight:	4	kg/m² (approx.)
Max. width:	3000	mm
Belt support:	Rollers, Flat	
Rating at 1% elongation:	10	N/mm
Advised pretension:	4 - 7	N/mm
Maximum allowable tension:	20	N/mm
Temperature range:	-10 to +90	°C
Minimum pulley diameters:		
Flexing:	75	mm
Backflexing:	75	mm

Special approval: FDA, 10/2011/EC + amendments

Applications: Conveyor belt for the food industry
Conveying of meat, fish and poultry products
Blue colour makes possible product contamination visible
Oil and grease resistant

Date of issue 17-12-2014-1

Your Partner In Belting Solutions

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nittacorporation.com