

Datasheet

Conveyor Belt



**NITTA CORPORATION
OF HOLLAND**

Berenkoog 25
1822 BH Alkmaar
The Netherlands

T: +31 (0)72 562 22 34
F: +31 (0)72 561 32 38

E: sales@nitta.nl
www.nittacorporation.com

- **NITTA BELT TYPE:**
2 XRAFP 03/W IM M
- **Nitta Japan code:**



Construction: 2 plies polyester, extremely rigid, antistatic

	TOP COVER	INNER LAYER	BOTTOM SIDE
Material:	PU	PU	Impregnated antistatic fabric
Thickness:	0,3		- mm (approx.)
Colour:	White	Transparent	-
Hardness:	92 Shore A		-
Profile:	matt		-

Total thickness:	2,2	mm (approx.)
Weight:	2,6	kg/m ² (approx.)
Max. width:	3000	mm
Belt support:	Sliderbed (Rollers), Flat	

Rating at 1% elongation:	9	N/mm
Advised pretension:	4 - 7	N/mm
Maximum allowable tension:	16	N/mm
Temperature range:	-10 to +80	°C

Minimum pulley diameters:	
Flexing:	40
Backflexing:	60

Special approval: Not applicable

Applications: -

Date of issue 20-03-2014-2

Your Partner In Belting Solutions

Data are valid at 15°C. Due to constant developments, Nitta reserves the right to make changes without prior notice. This issue succeeds all previous ones. Visit our website: www.nittacorporation.nl